

SOLID DOOR REFRIGERATORS **NATURAL Refrigerant**

- **Hydrocarbon refrigerants (R-290 / R-600a)**
With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).
- **Hot gas condensate system**
Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.
- **Cabinet construction**
E-Line refrigerator model boasts an AL exterior (galvanized steel top, bottom and back) and stainless steel interior with AL inside walls and door liners. It guarantees the utmost in cleanliness and long product life.
- **LED interior lighting**
- **Adjustable, heavy duty, PE (polyethylene) coated wire shelves**
- **High-density polyurethane insulation**
The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- **Self-contained system**
- **Standard 4" dia. swivel casters with locks on the front set**
- **Door locks standard**
- **Solid and sturdy grille design**
- **Top mount compressor**
- **Refrigerator holds 33°F ~ 38°F for the best in food preservation**



ER19-1-N6-V

ER47-2-N-V

- **Optional features**
 - Legs available for all models
 - Full and half pan racks available (except ER19-1-N6-V)

ER MODELS SPECIFICATIONS

ELECTRICAL DATA	ER19-1-N6-V	ER24-1-N6-V	ER47-2-N6-V	ER72-3-N-V
Voltage	115/60/1	115/60/1	115/60/1	115/60/1
Plug Type	ⓘ NEMA 5-15P	ⓘ NEMA 5-15P	ⓘ NEMA 5-15P	ⓘ NEMA 5-15P
Full Load Amperes	1.5	1.6	2.2	5.6
Compressor HP	1/8	1/8	1/5	1/2
Feed Wires with Ground	3	3	3	3
Cord Length (ft.)	9	9	9	9
Refrigerant	R-600a	R-600a	R-600a	R-290
DIMENSIONAL DATA				
# of Doors	1	1	2	3
# of Racks Accepted	-	1	2	3
Net Capacity (cu. ft.)	18.47	21.9	42.2	65.8
Ext.Dimension (L x D x H) (in.)	25 ¹ / ₄ x 31 ¹ / ₂ * x 72†	28 ³ / ₄ x 30 ³ / ₄ * x 78†	51 ³ / ₄ x 30 ³ / ₄ * x 78†	77 ³ / ₄ x 30 ³ / ₄ * x 78†
Int.Dimension (L x D x H) (in.)	21 ⁵ / ₈ x 27 ⁵ / ₈ x 58 ¹ / ₄	24 ³ / ₄ x 26 ¹ / ₂ x 60 ⁵ / ₈	47 ³ / ₄ x 26 ¹ / ₂ x 60 ⁵ / ₈	73 ⁷ / ₈ x 26 ¹ / ₂ x 60 ⁵ / ₈
# of Shelves	3	3	6	9
Shelf Size (L x D) (in.)	20 ¹ / ₂ x 23 ³ / ₄	24 x 23 ¹ / ₂	23 x 23 ¹ / ₂	23 x 23 ¹ / ₂ (L/R), 25 ³ / ₈ x 23 ¹ / ₂ (M)
Gross Weight (lbs.)	170	270	415	559

Design and specifications subject to change without notice. Most updated spec sheets are available at www.turboairinc.com.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2" for rear condensate enclosure. † Height does not include 5" for caster height.

- **WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor**